Parameter

Pixel 384 Field of view 14° Focal length 25n Base magnification 1.60 Focus range 1m	4x ~∞	plane 384×288 10.7°×8.0° 35mm 2.3x	640×480 17.7°×13.3° 35mm 1.38x
Field of view 14° Focal length 25n Base magnification 1.6c Focus range 1m Noise equivalent 5	×10.5° nm 4x ~∞	10.7°×8.0° 35mm	17.7°×13.3° 35mm
Focal length 25n Base magnification 1.6- Focus range 1m Noise equivalent <5	nm 4x ~∞	35mm	35mm
Base magnification 1.64 Focus range 1m Noise equivalent 5	4x ~∞		
Focus range 1m Noise equivalent 5	~∞	2.3x	1.38x
Noise equivalent			
	0mk@30℃		
	<50mk@30℃		
Frame rate 50H	50HZ		
Focus Mai	Manual focus		
Electronic zoom 2X,	2X, 3X, 4X		
Picture in Picture Yes	Yes		
Distance estimation Yes	Yes		
Wavelength range 8-1	8-14µm		
	WiFi real-time image transmission, support mobile APP image browsing, taking pictures, video and other functions		
Cross cursor Yes	Yes		
Hot spot tracking Yes			
Laser pointer Yes			
Display Col	Color LCOS1280*960 (eyepiece diopter adjustable)		
Image polarity Bla	Black hot, white hot, red hot, iron red		
Diopter adjustment Adj	Adjust by knob		
Battery type Lith	Lithium battery, rechargeable		
Battery working time 4 h	4 hours continuous		
Charging type USI	USB charging, power bank support		
External power supply DC!	DC5V/2A (Micro USB)		
Working temperature -20	-20°C- +50°C		
Storage temperature -40	°C-+60°C		
Protection level IP6	6		
Drop resistance 1 M			
Weight 0.4	5kg		
Size 200)*71*71mm		
Power connector Yes			
Video output PAL	PAL		
USB Ext	External charging		